



Gloucestershire Warwickshire Steam Railway Plc

Polycell Damp Seal Liquid

COSHH Assessment Details

Assessment Id:	COSHH-45213-36	Lead Assessor:	Michael Bell
Version No:	1	Published Date:	16 October 2023
Status:	Active	Review Date:	16 October 2026
Assessment Date:	14 October 2023	Approved By:	Kevin 'Kev' Jarvis

Substance Details

Substance Name:	Polycell Damp Seal Liquid	Substance Use:	Solvent borne coating for interior use
Manufacturer	Polycell	Emergency Tel No:	+44 1753 550 000
Address:	ICI Paints AkzoNobel, Wexham Road, Slough, Berkshire, SL2 5DS, U.K.		
Form Of Substance:	Liquid,	Routes of Exposure	Inhalation, Skin, Ingestion,
Storage and Handling	Keep cool		

Exposure Limits

WEL: 4 mg/m³

LEL: Unknown

SEL: 8 Hours

Substance Classifications



Irritant



Corrosive



Flammable

Health Phrases

H226 - Flammable liquid and vapour.
H318 - Causes serious eye damage.
H315 - Causes skin irritation.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.

Precautionary Phrases

P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 - IF IN EYES:
P310 - Immediately call a POISON CENTER/doctor/999
P312 - Call a POISON CENTER/doctor/999 if you feel unwell.



Gloucestershire Warwickshire Steam Railway Plc Polycell Damp Seal Liquid

P235 - Keep cool.

P501 - Dispose of contents/container via an approved disposal route

Required Personal Protection Equipment (PPE)



Gloves



Goggles

Control Measures

Current:

- Administrative - Follow manufacturers advice. - Effective

Potential:

No Potential Control Measures

Score Notes:

Assessment Score

Likelihood of Harm:

- 1) Very low probability – unlikely/once every 20 years

Severity of Harm:

- 1) Injury – no time off/minor first aid

Overall:

Low - Risk to be monitored to ensure it remains adequately controlled to an acceptable level.

Reference Documents

MSDS -

Appendix



Reference: UI-45215-902

Polycell Damp Seal Liquid Pic -
Picture