



Gloucestershire Warwickshire Steam Railway Plc

Locktite LB8201

COSHH Assessment Details

Assessment Id:	COSHH-45294-49	Lead Assessor:	Kevin Jarvis
Version No:	1	Published Date:	03 January 2024
Status:	Active	Review Date:	03 January 2027
Assessment Date:	03 January 2024	Approved By:	Kevin 'Kev' Jarvis

Substance Details

Substance Name:	Locktite LB8201	Substance Use:	Spray can lubricant
Manufacturer	Henkel	Emergency Tel No:	01442 278497
Address:	Wood Lane End, Hemel Hempstead. HP2 4RQ		
Form Of Substance:	Liquid, Mist, Vapour,	Routes of Exposure	Inhalation, Skin, Ingestion, Eyes,
Storage and Handling	Store in manufacturers container in a COSHH cupboard		
Exposure Limits			
WEL: 1.45 mg/m ³	LEL: Unknown	SEL: 1.81 mg/m ³	

Substance Classifications



Flammable

Health Phrases

H222 - Extremely flammable aerosol.

Precautionary Phrases

P251 - Do not pierce or burn, even after use.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P102 - Keep out of reach of children.

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Required Personal Protection Equipment (PPE)



Gloucestershire Warwickshire Steam Railway Plc Locktite LB8201



Gloves



Overalls



Goggles

Control Measures

Current:

- Administrative - Follow manufacturers advice. - Effective

Potential:

No Potential Control Measures

Score Notes:

Assessment Score

Likelihood of Harm:

1) Very low probability –
unlikely/once every 20 years

Severity of Harm:

2) Injury – up to 7 days lost time
days lost time

Overall:

Low - Risk to be monitored to
ensure it remains adequately
controlled to an acceptable level.

Reference Documents

Locktite LB8201 SDS - Safety Data Sheet

Appendix



Gloucestershire Warwickshire Steam Railway Plc Locktite LB8201



Reference: UI-45294-663
Locktite LB8201 Picture -