



Gloucestershire Warwickshire Steam Railway Plc Livedale Trimbond Adhesive

COSHH Assessment Details

Assessment Id:	COSHH-45295-92	Lead Assessor:	Kevin Jarvis
Version No:	1	Published Date:	04 January 2024
Status:	Active	Review Date:	04 January 2027
Assessment Date:	04 January 2024	Approved By:	Kevin 'Kev' Jarvis

Substance Details

Substance Name:	Livedale Trimbond Adhesive	Substance Use:	Spray can adhesive.
Manufacturer	AFT Aerosols Ltd	Emergency Tel No:	01782 285700
Address:	Unit 8, Berryhill Industrial Estate Berryhill Road Fenton Stoke-on-Trent ST4 2NL		
Form Of Substance:	Liquid, Mist, Vapour,	Routes of Exposure	Inhalation, Skin, Ingestion, Eyes,
Storage and Handling	Store in manufacturers packaging in a secure cupboard.		

Exposure Limits

WEL: 353 mg/m³

LEL: Unknown

SEL: 716 mg/m³

Substance Classifications



Serious long
term health
hazard



Flammable

Health Phrases

H222 - Extremely flammable aerosol.
H229 - Pressurised container. May burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H351 - Suspected of causing cancer

Precautionary Phrases

P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



Gloucestershire Warwickshire Steam Railway Plc Livedale Trimbond Adhesive

- P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P3 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 - IF exposed or concerned: Get medical advice/attention.
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.
P501 - Dispose of contents/container via an approved disposal route

Required Personal Protection Equipment (PPE)



Gloves



Respirator



Overalls



Goggles

Control Measures

Current:

- Administrative - Follow manufacturers instructions - Effective

Potential:

- Engineering - Consider LEV or fume extraction - Effective

Score Notes: The risk remains low.

Assessment Score

Likelihood of Harm:

- 1) Very low probability – unlikely/once every 20 years

Severity of Harm:

- 2) Injury – up to 7 days lost time days lost time

Overall:

Low - Risk to be monitored to ensure it remains adequately controlled to an acceptable level.

Reference Documents

Trimbond SDS - Safety Data Sheet

Appendix



Gloucestershire Warwickshire Steam Railway Plc Livedale Trimbond Adhesive



Reference: UI-45295-608
Trimbond picture -