



Gloucestershire Warwickshire Steam Railway Plc Evostik 528

COSHH Assessment Details

Assessment Id:	COSHH-44081-33	Lead Assessor:	Kevin Jarvis
Version No:	3	Published Date:	03 September 2024
Status:	Active	Review Date:	03 September 2027
Assessment Date:	03 September 2024	Approved By:	Kevin Jarvis

Substance Details

Substance Name:	Evostik 528	Substance Use:	Instant contact high strength adhesive.
Manufacturer	Bostik	Emergency Tel No:	01785 272650
Address:	BOSTIK LIMITED, COMMON ROAD, STAFFORD, STAFFORDSHIRE, ST16 3EH		
Form Of Substance:	Liquid, Vapour,	Routes of Exposure	Inhalation, Skin, Ingestion, Eyes,
Storage and Handling	Store in manufacturers containers in a COSHH Cupboard		

Exposure Limits

WEL: Unknown **LEL:** 1210 mg/m³ **SEL:** 3620 mg/m³

Substance Classifications



Harmful



Flammable



Dangerous to
the
enviroment

Health Phrases

H225 - Highly flammable liquid and vapour.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary Phrases

P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P305 + P351 + P3 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.



Gloucestershire Warwickshire Steam Railway Plc Evostik 528

P501 - Dispose of contents/container via an approved disposal route
P233 - Keep container tightly closed.

Required Personal Protection Equipment (PPE)



Gloves



Respirator



Goggles

Control Measures

Current:

- Administrative - Follow manufacturers control measures - Effective

Potential:

- Engineering - Use additional fume extraction. - Effective

Score Notes:

Assessment Score

Likelihood of Harm:

2) Low probability – seldom/once every 5 years

Severity of Harm:

2) Injury – up to 7 days lost time

Overall:

Low - Risk to be monitored to ensure it remains adequately controlled to an acceptable level.

Reference Documents

Evostik 528 Data Sheet - Evostik 528 Data Sheet

Appendix



Gloucestershire Warwickshire Steam Railway Plc Evostik 528



Reference: UI-44081-421

Evostik 528 picture - Evostik 528
picture