



Gloucestershire Warwickshire Steam Railway Plc FryStandard Fryolux Paint

COSHH Assessment Details

Assessment Id:	COSHH-44081-95	Lead Assessor:	Kevin Jarvis
Version No:	3	Published Date:	03 September 2024
Status:	Active	Review Date:	03 September 2027
Assessment Date:	03 September 2024	Approved By:	Kevin Jarvis

Substance Details

Substance Name:	FryStandard Fryolux Paint	Substance Use:	General purpose industrial solder
Manufacturer	The Solder Connection	Emergency Tel No:	01291 624400
Address:	Unit 5 Severn Link Distribution Centre, Chepstow, Monmouthshire, NP16 6UN		
Form Of Substance:	Liquid, Vapour,	Routes of Exposure	Inhalation, Skin, Ingestion, Eyes,
Storage and Handling	Store in manufacturers container in a COSHH cupboard.		

Exposure Limits

WEL: 0.1 mg/m³

LEL: Unknown

SEL: 0.2 mg/m³

Substance Classifications



Toxic



Corrosive



Dangerous to
the
enviroment

Health Phrases

H302 - Harmful if swallowed.
H314 - Causes severe skin burns and eye damage.
H332 - Harmful if inhaled.
H335 - May cause respiratory irritation.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary Phrases

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash thoroughly after handling.
P270 - Do no eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P312 - IF SWALLOWED: Call a POISON CENTER/doctor/999 if you feel unwell.

COSHH - FryStandard Fryolux Paint - Generated 24/05/2026 at 14:57:43



Gloucestershire Warwickshire Steam Railway Plc FryStandard Fryolux Paint

P301 + P330 + P3 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303 + P361 + P3 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P3 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER/doctor/999 if you feel unwell.
P321 - Specific treatment. Refer to MSDS
P330 - Rinse mouth.
P363 - Wash contaminated clothing before reuse.
P391 - Collect spillage.
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container via an approved disposal route

Required Personal Protection Equipment (PPE)



Gloves



Overalls



Goggles

Control Measures

Current:

- Administrative - Follow manufacturers control measures - Effective

Potential:

- Engineering - Consider fume extraction - Effective

Score Notes:

Assessment Score

Likelihood of Harm:

2) Low probability – seldom/once every 5 years

Severity of Harm:

2) Injury – up to 7 days lost time days lost time

Overall:

Low - Risk to be monitored to ensure it remains adequately controlled to an acceptable level.

Appendix



Gloucestershire Warwickshire Steam Railway Plc FryStandard Fryolux Paint



Reference: UI-44081-663
Fryolux Solder Paint picture -
Fryolux Solder Paint picture