Gloucestershire Warwickshire Steam Railway Plc

Johnstones Trade Professional Undercoat

COSHH Assessment Details

Assessment Id:	COSHH-44194-29	**Lead Assessor:**	Kevin Jarvis
Version No:	3	**Published Date:**	03 September 2024
Status:	Active	**Review Date:**	03 September 2027
Assessment Date:	03 September 2024	**Approved By:**	Kevin Jarvis

Substance Details

Substance Name:	Johnstones Trade Professional Undercoat	**Substance Use:**	General purpose undercoat paint.
Manufacturer	PPG Architectural Coatings UK Ltd	**Emergency Tel No:**	01924 354000
Address:	Huddersfield Road, Birstall, West Yorkshire. WF17 9XA		
Form Of Substance:	Liquid, Vapour,	**Routes of Exposure**	Inhalation, Skin, Ingestion, Eyes,
Storage and Handling	Store in manufacturers container in a COSHH cupboard.		

Exposure Limits

WEL: 5 mg/m3 **LEL:** Unknown **SEL:** 10 mg/m3

Substance Classifications



Flammable

Health Phrases

H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H312 - Harmful in contact with skin.
H318 - Causes serious eye damage.
H317 - May cause an allergic skin reaction.
H351 - Suspected of causing cancer
H361 - Suspected of damaging fertility or the unborn child <state specific effect if known>

Precautionary Phrases

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P235 - Keep cool.
P501 - Dispose of contents/container via an approved disposal route

P303 + P361 + P3 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Required Personal Protection Equipment (PPE)


Gloves


Overalls


Goggles

Control Measures

Current:
• Administrative - Follow manufacturers advice - Effective
Potential:
No Potential Control Measures
Score Notes:

Assessment Score

Liklihood of Harm:
2) Low probability – seldom/once every 5 years

Severity of Harm:
2) Injury – up to 7 days lost time
days lost time

Overall:
Low - Risk to be monitored to ensure it remains adequately controlled to an acceptable level.

Reference Documents

Johnstones trade Professional Undercoat data sheet - Johnstones trade Professional Undercoat MSDS

Appendix



Reference: UI-44194-439
Johnstones trade Professional Undercoat - Johnstones trade Professional Undercoat picture