Gloucestershire Warwickshire Steam Railway Plc

Masons P Type Paint

COSHH Assessment Details

Assessment Id:	COSHH-44146-97	**Lead Assessor:**	Kevin Jarvis
Version No:	3	**Published Date:**	03 September 2024
Status:	Active	**Review Date:**	03 September 2027
Assessment Date:	03 September 2024	**Approved By:**	Kevin Jarvis

Substance Details

Substance Name:	Masons P Type Paint	**Substance Use:**	Paint used primarily for diesel locomotives
Manufacturer	AkzoNoble	**Emergency Tel No:**	+31(0)71 3086944
Address:	Akzo Nobel Car Refinishes bv Rijksstraatweg 31 2171 AJ Sassenheim The Netherlands		
Form Of Substance:	Liquid, Vapour,	**Routes of Exposure**	Inhalation, Skin, Ingestion, Eyes,
Storage and Handling	Store in manufacturers containers in a cool COSHH cabinet		

Exposure Limits

WEL: 500 mg/M3 **LEL:** Unknown **SEL:** Unknown

Substance Classifications



Harmful



Serious long term health hazard



Flammable



Dangerous to the enviroment

Health Phrases

H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.
H372 - Causes damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects.

Precautionary Phrases

P102 - Keep out of reach of children.
P103 - Read label before use.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P262 - Do not get in eyes, on skin, or on clothing.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P403 + P235 - Store in a well-ventilated place. Keep cool.
P312 - Call a POISON CENTER/doctor/999 if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P401 - Store in accordance with MSDS
P501 - Dispose of contents/container via an approved disposal route

Required Personal Protection Equipment (PPE)


Gloves


Overalls


Goggles

Control Measures

Current:
• Administrative - Follow manufacturers advice - Effective
Potential:
No Potential Control Measures
Score Notes:

Assessment Score

Liklihood of Harm:
2) Low probability – seldom/once every 5 years

Severity of Harm:
3) Injury - > 7 days lost time + RIDDOR reportable

Overall:
Medium - Risk to be minimised and controlled so far as is reasonably practical.

Reference Documents

P Type MSDS - Material Safety Data Sheet