

# Gloucestershire Warwickshire Steam Railway Plc Rustoleum 3301 Super adhesive Primer Activator

#### **COSHH Assessment Details**

Assessment Id: COSHH-44392-78 Lead Assessor: Kevin Jarvis

Version No:2Published Date:03 September 2024Status:ActiveReview Date:03 September 2027

Assessment Date: 03 September 2024 Approved By: Kevin Jarvis

**Substance Details** 

Substance Name: Rustoleum 3301 Super Substance Use: Industrial Coatings Primer

adhesive Primer Activator

Manufacturer Rust-Oleum Europe Emergency Tel No: 0207 8581228

Address: Kolenbergstraat 23,

Activator

B3545 Zelem, Belgium

Form Of Substance: Liquid, Vapour, Routes of Exposure Inhalation, Skin, Ingestion,

Eyes,

**Storage and** Store in manufacturers container in a COSHH cupboard **Handling** 

**Exposure Limits** 

WEL: 12 mg/m3 LEL: Unknown SEL: 0.75 mg/m3

#### **Substance Classifications**







Dangerous to the environment

#### **Health Phrases**

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H411 - Toxic to aquatic life with long lasting effects.

### **Precautionary Phrases**

P103 - Read label before use.

P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P273 - Avoid release to the environment.

P391 - Collect spillage.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

COSHH - Rustoleum 3301 Super adhesive Primer Activator - Generated 08/12/2025 at 16:24:16

Page 1 of 3



## Gloucestershire Warwickshire Steam Railway Plc Rustoleum 3301 Super adhesive Primer Activator

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention. P501 - Dispose of contents/container via an approved disposal route

## **Required Personal Protection Equipment (PPE)**







#### **Control Measures**

#### **Current:**

• Administrative - Follow manufacturers advice. - Effective <u>Potential:</u>

No Potential Control Measures Score Notes:

#### **Assessment Score**

Liklihood of Harm: 2) Low probability – seldom/once every 5 years Severity of Harm: 2) Injury – up to 7 days lost time days lost time

Overall:
Low - Risk to be monitored to
ensure it remains adequately
controlled to an acceptable level.

## **Reference Documents**

Mathys Rustoleum 3301 Super Adhesive Primer Activator Data Sheet - Mathys Rust-oleum 3301 Super Adhesive Primer Activator MSDS

## **Appendix**



# Gloucestershire Warwickshire Steam Railway Plc Rustoleum 3301 Super adhesive Primer Activator



Reference: UI-44392-853
Mathys Rustoleum 3301 Super
Adhesive Primer Activator - Mathys
Rustoleum 3301 Super Adhesive
Primer Activator